

A Sampler of Form Elements

```
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
<title>Sample Form</title>
</head>
<body>
<h2>Sample Form</h2>
<form action="procform.html" method="get">
<table summary="formatting table" cellspacing="5">
<colgroup span="1" align="right"></colgroup>
<colgroup span="1" align="left"></colgroup>
<tr>
<td><label for="text1">Text Input:</label></td>
<td><input type="text" name="text1" value="Sample text" length="40" maxlength="80"></input></td>
</tr>
<tr>
<td><label for="text2">Read-Only Text Input:</label></td>
<td><input type="text" name="text2" value="Read-Only Text" length="40" maxlength="80" readonly="readonly"></input></td>
</tr>
<tr>
<td><label for="password1">Password Input:</label></td>
<td><input type="password" name="password1" value="" length="40" maxlength="80"></input></td>
</tr>
<tr>
<td><label for="checkbox1">Checkbox Input:</label></td>
<td><input type="checkbox" name="checkbox1" value="yes"></input></td>
</tr>
<tr>
<td><label for="checkbox2">Checkbox Input:</label></td>
<td><input type="checkbox" name="checkbox2" value="yes" checked="checked"></input></td>
</tr>
<tr>
<td><label for="radio1">Radio Buttons Input:</label></td>
<td><input type="radio" name="radio1" value="option1"></input>
<input type="radio" name="radio1" value="option2"></input>
<input type="radio" name="radio1" value="option3"></input></td>
</tr>
<tr>
<td><label for="radio2">Radio Buttons Input:</label></td>
<td><input type="radio" name="radio2" value="option1" checked="checked"></input>
<input type="radio" name="radio2" value="option2"></input>
<input type="radio" name="radio2" value="option3"></input></td>
</tr>
<tr>
<td><label for="file">File Input:</label></td>
<td><input type="file" name="file1" value="filename"></input></td>
</tr>
<tr>
<td><label for="button1">Button Input:</label></td>
<td><input type="button" name="button1" value="A Button"></input></td>
</tr>
<tr>
<td><label for="image1">Image Button Input:</label></td>
<td><input type="image" name="image1" value="An Image" src="g/button1.gif"></input></td>
</tr>
<tr>
<td><label for="reset1">Reset Button Input:</label></td>
<td><input type="reset" name="reset1" value="A Reset Button"></input></td>
</tr>
<tr>
<td><label for="submit1">Submit Button Input:</label></td>
<td><input type="submit" name="submit1" value="A Submit Button"></input></td>
</tr>
<tr>
<td><label for="textareal">Text Area:</label></td>
<td><textarea cols="60" rows="10" name="textareal">Sample text.</textarea></td>
</tr>
<tr>
<td><label for="select1">Select:</label></td>
<td><select name="select1">
<option value="option1" label="Option 1a">Option 1b</option>
<option value="option2" selected="selected">Option 2</option>
<option value="option3">Option 3</option>
<optgroup>
<option value="option4">Option 4</option>
<option value="option5">Option 5</option>
</optgroup>
</select></td>
</tr>
<tr>
<td><label for="button2">Button:</label></td>
<td><button type="button" name="button2" value="button2">Another Button</button></td>
</tr>
<tr>
<td><label for="button3">Button:</label></td>
<td><button type="button" name="button3" value="button3">
</button></td>
</tr>
<tr>
<td><label for="reset2">Reset Button:</label></td>
<td><button type="reset" name="reset2" value="reset2">Another Reset Button</button></td>
</tr>
<tr>
<td><label for="submit2">Submit Button:</label></td>
<td><button type="submit" name="submit2" value="submit2">Another Submit Button</button></td>
</tr>
<tr>
<td><label for="hidden1">Hidden Input:</label></td>
<td><input type="hidden" name="hidden1" value="secret"></input></td>
</tr>
</table>
</form>
</body>
</html>
```